

## DFWLID

"DFWLID": STAINLESS STEEL WEIGHT INDICATOR WITH LARGE DIGITS LCD



Easy to programme and use, versatile and high performing IP68 stainless steel weight indicator. The 40mm big colored backlit display gives a clear view of the weight and helps the user during the weighing operations. The wide range of available functions and interfaces make it suitable for multiple industrial and commercial weighing applications, such as floor scales, mobile weighing, etc. Fitted with built-in rechargeable battery. CE-M approvable (OIML R-76/EN 45501).

Working in cooperation with:

**SCALETEC LTD**

903 TREMAINE AVENUE - 4414 - PALMERSTON NORTH - NEW ZEALAND  
Tel. 0064 6 3765041  
tonyj@scaletec.co.nz

**The best solution  
for advanced industrial  
applications**

## MAIN FEATURES

- 5-key functional waterproof keypad.
- Backlit 40mm LCD display with 6 high contrast digits with icons for showing the active functions.
- Color and brightness of the backlighting, customizable from Setup.
- Easy to clean stainless steel IP68 case, resistant to harsh and corrosive environments.
- Dimensions: 243x145x78,4mm.
- Suitable for use on the table, column, or wall.
- A/D 24 bit, 4 channel converter, max. 200 conv./sec. autoselect, and up to 8 signal linearisation points.
- Up to 10.000e or multirange 3 x 3000e @ 0,3  $\mu$ V/e in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points.
- Connection with up to 8 load cells with input resistance equal to 350 Ohm or up to 16 cells of 700 Ohm each.
- Digital calibration and Set-Up from keypad or from PC through DINITOOLS.
- Power supply through built-in rechargeable battery, with 40h operating time, and fitted with external battery charger.
- "DFWLIP" power source through internal power supply (version with no internal battery provided).

## FUNCTIONS

- MAIN FUNCTIONS:
  - Zeroing
  - Automatic tare
  - Presetable tare
  - Printing in 1, 2 or 3 copies
  - Data transmission to PC
- OPERATING MODES:
  - High Resolution Weighing x 10
  - Net/Gross or lb/kg conversion
  - Accumulation
  - Formula weighing
  - +/- Checkweighing
  - Percentage weighing
  - Approved transmission of the weight to PC/PLC (with Alibi memory ALMEM option)
  - Counting
  - Hold
- OPTIONAL FUNCTIONS:
  - PEAK, detection of weight peaks (code DFWPK)
  - Newton to Kg converter (code DFWPK)
  - Input-output (on request)
- Access to the user menu is gained using the dedicated key\* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

\* *These quick access keys to the menus can be blocked by configuring a dedicated password.*

## I/O SECTION

- RS232/C bidirectional port on RJ connector for quick connection (or optional RS485) on screw terminal, configurable for PC, PLC, or additional remote display.
- RS232/C bidirectional port configurable for connection to printer or labeller.

## DETAIL 1

### TOLERANCE +/-

OUT OF TOLERANCE - HIGH



INTOLERANCE - TARGET OK



OUT OF TOLERANCE - LOW



The color of the backlight, in the tolerance control function, automatically changes depending on the weight.



[www.diniargeo.com](http://www.diniargeo.com)

“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano - Modena - Italy  
Tel. +39.0536 843418

**SCALETEC LTD**

903 TREMAINE AVENUE - 4414 - PALMERSTON NORTH - NEW ZEALAND

Tel. 0064 6 3765041

[tonyj@scaletec.co.nz](mailto:tonyj@scaletec.co.nz)

SALES AND TECHNICAL ASSISTANCE SERVICE