



W75

PRODUCT INFORMATION

- ✓ OIML R76:2006 class III
- ✓ Extra large 50mm digit size wide angle LCD display with LED backlight
- ✓ Heavy duty construction design withstand harsh industrial operation
- ✓ Overload and shock protection
- ✓ High speed 24 bits multiplexed delta-sigma A/D converter
- ✓ Approved dual weighing range
- ✓ Supporting kg/lb conversion and simple piece counting
- ✓ 3 color backlight and alarm for check weighing function
- ✓ Functions including: power on zero tracking, manual zero, full subtractive tare, auto tare, preset tare, automatic continuous tare, data accumulation, digital motion filtering, animal weighing, simple piece counting, check weighing and battery power level indicator
- ✓ Built-in rechargeable battery for 210 hours operating time
- ✓ Platter B size: 330 x 450 mm / F size: 400 x 500 mm
- ✓ Options available: RS-232 interface



Model	Capacity	Readability
W75-B30	15 / 30 kg	5 / 10 g
W75-B60	30 / 60 kg	10 / 20 g
W75-F60	30 / 60 kg	10 / 20 g
W75-F150	60 / 150 kg	20 / 50 g
Operating Environment	10°C ~40°C (14°F ~104°F), Non-condensed. R.H. ≤85%	
Power Source	By Built-in Rechargeable Battery or Power Adaptor	
Options Available	RS232 Interface, RS485, Real Time Clock, 4 Channels Relay Output	



UNIVERSAL WEIGHT ELECTRONICS CO., LTD.

4th FLOOR, NO.53, BAOXING ROAD, XINDIAN DISTRICT, NEW TAIPEI CITY 231, TAIWAN (R.O.C)

+886-2-29180121 | int@uwe.com.tw | www.uwe.com.tw